

CLAIMS

1. Method for use in a wireless network, comprising the steps of:
classifying packets (16) destined for various bearers of various mobile
terminals according to differing classes,

5 storing (20) said classified packets according to said differing classes and
according to said various bearers of various destination mobile terminals,

scheduling (22) some or all of said stored packets for possible transmission
according to said various bearers of various destination mobile terminals during a
cycle of a packet scheduler,

10 scheduling (10) some or all of said stored packets that have been scheduled for
possible transmission for actual transmission according to said differing classes, and
transmitting (28) said stored packets scheduled for actual transmission during
transmission time intervals occurring during said cycle of said packet scheduler.

15 2. The method of claim 1, wherein said step of scheduling (10) some or all
of said stored packets that have been scheduled for possible transmission for actual
transmission according to said differing classes, comprises the step of scheduling
equal amounts of data for transfer from said different classes.

20 3. The method of claim 1, wherein said step of scheduling (10) some or all
of said stored packets that have been scheduled for possible transmission for actual
transmission according to said differing classes, comprises the steps of determining
transmission capacity of a transmission time interval and dividing said capacity into
equal portions, one portion for each of said differing classes.

25

09648781-082800

5

classes,

allocating the overall capacity of the transmission time interval based on said

15

10

determining a capacity of a transmission time interval, and

15

20

33

7. The method of claim 1, wherein said step of scheduling (10) some or all of said stored packets that have been scheduled for possible transmission for actual transmission according to said differing classes, further comprises the steps of:

- 5 determining from a priority table priorities of said packets stored according to said differing classes,
- determining a capacity of a transmission time interval, and
- allocating said capacity based on said priorities.

8. The method of claim 1, wherein said differing classes are indicative of
10 quality-of-service requested for said packets in transit outside said wireless network before arriving at said wireless network, said method further comprising the steps of:

- determining if said packets actually received said requested quality-of-service in transit outside said wireless network, and wherein said step of classifying comprises the step of classifying said packets according to said requested quality-of-service if
15 said packets actually received the requested quality-of-service in transit outside said wireless network, and otherwise classifying said packets according to a quality of service actually experienced by said packets in transit outside said wireless network.

9. Apparatus for use in a wireless network, comprising:
20 packet classifier (16) for classifying packets destined for various bearers of various mobile terminals according to differing classes,
packet storage medium (20) for storing said classified packets according to said differing classes and according to said various bearers of various destination mobile terminals,
25 packet scheduler (22) for scheduling some or all of said stored packets for possible transmission according to said various bearers of various destination mobile terminals during a cycle of said packet scheduler,

quality-of-service (QoS) scheduler (10) for scheduling some or all of said stored packets that have been scheduled for possible transmission for actual transmission according to said differing classes, and

transmitter for transmitting some or all of said packets scheduled for actual
5 transmission during transmission time intervals occurring during said cycle of said packet scheduler.

10. The apparatus of claim 9, wherein said QoS scheduler comprises means for scheduling equal amounts of data for transfer from said different classes.

10

11. The apparatus of claim 9, wherein said QoS scheduler comprises means for determining transmission capacity of a transmission time interval and means for dividing said capacity into equal portions, one portion for each of said differing classes.

15

12. The apparatus of claim 9, wherein said QoS scheduler comprises:
means for determining service types of said differing classes,
means for determining capacity of a transmission time interval, and
means for allocating the overall capacity of the transmission time interval based
20 on said service types.

20

13. The apparatus of claim 9, wherein said QoS scheduler comprises:
means for measuring amounts of packets stored according to said differing
classes,
25 means for determining a capacity of a transmission time interval, and
means for dividing the capacity of the transmission time interval according to
said measured buffer levels.

25

008280" T8784960

Subs
a1

14. The apparatus of claim 9, wherein said QoS scheduler comprises:
means for determining priorities of said packets stored according to said
differing classes,

5 means for determining capacity of a transmission time interval, and
means for allocating said capacity based on said priorities.

15. The apparatus of claim 9, wherein said QoS scheduler comprises:
means for determining from a priority table priorities of said packets stored
10 according to said differing classes,
means for determining a capacity of a transmission time interval, and
means for allocating said capacity based on said priorities.

16. The apparatus of claim 9, wherein said differing classes are indicative
15 of quality-of-service requested for said packets in transit outside said wireless network
before arriving at said wireless network, said apparatus further comprising:

means for determining if said packets actually received said requested quality-
of-service in transit outside said wireless network, and wherein said packet classifier
comprises means for classifying said packets according to said requested quality-of-
20 service if said packets actually received the requested quality-of-service in transit
outside said wireless network, and otherwise for classifying said packets according to a
quality of service actually experienced by said packets in transit outside said wireless
network.

Subs
a1

17. Method, comprising the steps of:

receiving a packet in a first network from a second network, said packet having information relating to a quality-of-service requested for said packet,

determining if said packet actually requires said requested quality-of-service,

5 and

classifying said packet according to said requested quality-of-service and providing said packet with said requested quality-of-service over said first network, otherwise classifying said packet according to a quality-of-service actually experienced by said packet over said second network and providing said packet with a quality-of-

10 service corresponding to said quality-of-service actually experienced by said packet over said second network.

18. The method of claim 17, further comprising the step of:

notifying a sender of said packet of said quality-of-service actually

15 experienced by said packet over said second network.

Subs
a1

19. Apparatus for use in a wireless network, comprising:

means for receiving a packet in a first network from a second network, said packet having information relating to a quality-of-service requested for said packet;

20 means for determining if said packet actually requires said requested quality-of-service; and

means for classifying said packet according to said requested quality-of-service and providing said packet with said requested quality-of-service over said first network, otherwise classifying said packet according to a quality-of-service actually

25 experienced by said packet over said second network and providing said packet with a quality-of-service corresponding to said quality-of-service actually experienced by said packet over said second network.

20. The apparatus of claim 19, further comprising:

means for notifying a sender of said packet of said quality of service actually experienced by said packet over said second network.

09648781.082800